

CORDLESS

PNEUMATIC

DRILLING

ROTARY & DEMOLITION

FASTENING

GRINDING & CUTTING

POLISHING / SANDING

SAWING

PLANING / ROUTING

AIR DISPLACEMENT

ENGINE

ACCESSORIES

QUICK REFERENCE GUIDE FOR SCREW DRIVERS

Model	No Load Speed	Power Input	Applicable Fasteners				Weight
			Machine Screw	Self Drilling Screw	Drywall Screw	Wood Screw	
W6VB3	0 – 2,600 (min-1)	620W	6mm	6mm	6mm	5.8mm	1.5kg
W8VB2	0 – 1,700 (min-1)	620W	6mm	8mm	6mm	6.2mm	1.5kg

SCREW DRIVERS

W6VB3 6mm TEK Screw Driver 05275804



- Ideal for self-drilling / TEK screws
- Variable speed to suit multiple drilling applications
- Forward and reversible for convenience
- Aluminium cover and inner cover for increased durability
- One motion detachable locator for easy adjustment
- Soft protector around aluminium gear cover to prevent marks on work piece
- Low operation noise of only 76db for increased user comfort and safety

Specifications

Auto Stop 999091

Bit shank	6.35mm hex
Capacity	Machine screw: 6mm Drywall screw: 6mm Self-drilling screw: 6mm Wood screw: 5.8mm
Input power	620W
No load speed	0 – 2,600 (min-1)
Length	312mm
Weight	1.5kg
Standard accessories	Magnetic hex socket and sub stopper



W8VB2 8mm Tek Screw Driver 05275821



- Ideal for self-drilling / TEK screws
- Variable speed to suit multiple drilling applications
- Forward and reversible for convenience
- Aluminium cover and inner cover for increased durability
- One motion detachable locator for easy adjustment
- Soft protector around aluminium gear cover to prevent marks on work piece
- Low operation noise of only 76db for increased user comfort and safety

Specifications

Auto Stop 999091

Bit shank	6.35mm hex
Capacity	Machine Screw: 6mm Dry wall screw: 6mm Self drilling screw: 8mm Wood screw: 6.2mm
Input power	620W
No load speed	0 – 1,700 (min-1)
Length	312mm
Weight	1.5kg
Standard accessories	Magnetic hex socket and sub stopper



ACCESSORIES FOR SCREW DRIVERS

	Part No.	Description	For Model	Barcode
	982563Z	Bit Holder Non-Magnetic	W8VB	4966375536819
	752398	Magnetic Bit Holder (41L)	W6VA4, W6VB3, W8VB, W8VB2	8717472814098
	985322	5/16" Hex Socket Magnetic	W6VB3, W8VB, W8VB2	4966375115793
	317670	Sub Locator 3/8"	W8VB	4966375287292
	317671	Sublocator for 5/16" Hex Socket	W6VA4, W6VB3, W8VB, W8VB2	4966375287308

QUICK REFERENCE GUIDE FOR IMPACT WRENCHES

Model	Power Input	No Load Speed	Impact Rate	Torque	Capacity		Weight
					Ordinary Bolt	High Tension Bolt	
WR16SA(H7)	420W	1,700 (min-1)	1,900 (min-1)	300Nm	12 -22mm	12-16mm	2.9kg
WR22SA	850W	1,800 (min-1)	2,000 (min-1)	610Nm	14-24mm	16-22mm	4.8kg

IMPACT WRENCHES

Specifications

999021



Capacity	Ordinary bolt: 12 – 22mm High tension bolt: 12 – 16mm
Input power	420W
Torque	300Nm
No load speed	1,700 (min-1)
Impact rate	1,900 (min-1)
Weight	2.9Kg
Length	258mm
Standard accessories	Side handle. Socket not included

- Powerful 420W motor with a maximum torque of 300Nm for high torque applications
- Rocker switch for easy forward and reverse
- Large bumper protects the outer frame and helps protects work pieces
- Soft grip handle for easy handling and user comfort



WR16SA(H7)
12.7mm Impact Wrench
06450283



Specifications

999043



Capacity	Ordinary bolt: 14 – 24mm High tension bolt: 16 – 22mm
Input power	850W
Torque	610Nm
No load speed	1,800 (min-1)
Impact rate	2,000 (min-1)
Weight	4.8kg
Length	303mm
Standard accessories	Side handle and carry case. Socket not included

- Powerful 850W motor with a maximum torque of 610Nm for high torque applications
- Rocker switch for easy forward and reverse
- Large bumper protects the outer frame and helps protects work pieces
- Soft grip handle for easy handling and user comfort
- Aluminium die-cast body for longer service life



WR22SA
19mm Impact Wrench
00097709



CORDESS

PNEUMATIC

DRILLING

ROTARY &
DEMOLITION

FASTENING

GRINDING
& CUTTING

POLISHING /
SANDING

SAWING

PLANING /
ROUTING

AIR
DISPLACEMENT

ENGINE

ACCESSORIES