

## PNEUMATICS SELECTION CHART

Tool Type	Max Fixing Length (mm)	Model	Type Of Fixing	Trigger Function		Fastener Capacity	Heavy Duty Application
				Single Fire	Bump Fire		
Stapler	38	N3804AB3(H2)	6000 Series Staples	•	•	100	•
Brad Nailer	32	NT32AE2(H2)	C1 Series Brad Nails	•	•	100	•
Brad Nailer	50	NT50AE2(H2)	C1 Series Brad Nails	•	•	100	•
Finish Nailer	65	NT65M2(H2)	C Series Finish Nails	•	•	100	•
Finish Nailer	65	NT65MA4(H2)	DA Series Finish Nails	•	•	100	•
Framing Nailer	90	NR90AD(H2)	34° Clipped Head Framing Nails	•	•	95 (50x2.80mm) 90 (75x3.06mm) 85 (90x3.30mm)	•
Coil Nailer	65	NV65AF3	16° Wire Collated or 15° Plastic Collated Coil Nails	•	•	200 – 400	•
T & F Nailer	65	NT65AB	T & F Series Nails		•	120	•
Concrete Nailer	65	NC65AC	Hitachi CV Series Nails		•	54	•

## STAPLER

### N3804AB3(H2)

**38mm Narrow Crown Stapler**  
08268450



- Dual function trigger for single fire & bump fire
- Tool-less depth dial for flush, proud or deep driving
- 360° adjustable exhaust directs air away from user
- Tool-less release for clearing jammed staples
- Replacement O-Ring kit available (886375)

■ Applicable staple sizes: mm (in.)

	L	A	B	C
	13 (1/2)			
	16 (5/8)			
	19 (3/4)			
	22 (7/8)			
	25 (1)	3.5 (.138)	1.08 (.043)	1.25 (.049)
	29 (1-1/8)			
	32 (1-1/4)			
	38 (1-1/2)			

### Specifications

Pressure range	70 – 120 psi
Capacity	100 staples
Dimensions	263 x 235mm
Weight	1.0kg
Fastener series	18 gauge 6000 series staples
Standard accessories	Nose protector, safety glasses and carry case



## BRAD NAILERS

### NT32AE2(H2)

**32mm C1 Series Brad Nailer**  
08268331



- Dual function trigger for single fire & bump fire
- Tool-less depth dial for flush, proud or deep driving
- 360° adjustable exhaust directs air away from user
- Tool-less release for clearing jammed nails
- Reload window enables the user to see remaining nails
- Replacement O-Ring kit available (886375)

■ Applicable nail sizes: mm (in.)

	L
	16(5/8) – 32(1-1/4)
A	1.9(.075)
B	1.0(.039)
C	1.1(.043)
D	1.25(.049)

### Specifications

Pressure range	70 – 120 psi
Capacity	100 nails
Dimensions	254 x 197mm
Weight	900g
Fastener series	18 gauge C1 series brad nails
Standard accessories	Nose protector, safety glasses and carry case



### NT50AE2(H2)

**50mm C1 Series Brad Nailer**  
08268348



- Dual function trigger for single fire & bump fire
- Tool-less depth dial for flush, proud or deep driving
- 360° adjustable exhaust directs air away from user
- Tool-less release for clearing jammed nails
- Reload window enables the user to see remaining nails
- Replacement O-Ring kit available (886375)

■ Applicable nail sizes: mm (in.)

	L
	16(5/8) – 50(2)
A	1.9(.075)
B	1.0(.039)
C	1.1(.043)
D	1.25(.049)

### Specifications

Pressure range	70 – 120 psi
Capacity	100 nails
Dimensions	254 x 233mm
Weight	1.0kg
Fastener series	18 gauge C1 series brad nails
Standard accessories	Nose protector, safety glasses and carry case



## FINISH NAILERS

### Specifications

Pressure range	70 – 120 psi
Capacity	100 nails
Dimensions	295 x 285mm
Weight	1.7kg
Fastener series	16 gauge C series finish nails
Standard accessories	Nose protector, safety glasses and carry case



- Dual function trigger for single fire & bump fire
- Tool-less depth dial for flush, proud or deep driving
- 360° adjustable exhaust directs air away from user
- Tool-less release for clearing jammed nails
- Unique integrated air duster acts as a dust gun
- Replacement O-Ring kit available (885914)

#### ■Applicable nail sizes:

	mm (in.)
L	25(1) – 65(2-1/2)
A	2.8(.110)
B	1.4(.054)
C	1.3(.050)
D	1.65(.065)

### NT65M2(H2) 65mm C Series Finish Nailer

08268365



### Specifications

Pressure range	70 – 120 psi
Capacity	100 nails
Dimensions	344 x 304mm
Weight	1.9kg
Fastener series	15 gauge DA series finish nails
Standard accessories	Nose protector, safety glasses and carry case



- Dual function trigger for single fire & bump fire
- Tool-less depth dial for flush, proud or deep driving
- 360° adjustable exhaust directs air away from user
- Tool-less release for clearing jammed nails
- Unique integrated air duster acts as a dust gun
- Replacement O-Ring kit available (886376)

#### ■Applicable nail sizes:

	mm (in.)
L	32(1-1/4) – 65(2-1/2)
A	2.4(.095)
B	3.0(.12)
C	1.1(.045)
D	1.8(.072)

### NT65MA4(H2) 65mm DA Series Finish Nailer

08268382



## FRAMING NAILER

### Specifications

Pressure range	70 – 120 psi
Capacity	95 nails : 50 x 2.80mm 90 nails : 75 x 3.06mm 85 nails : 90 x 3.30mm
Dimensions	462 x 322mm
Weight	3.2kg
Fastener series	34° paper collated clipped head framing nails
Standard accessories	Safety glasses



- Dual function trigger for single fire & bump fire
- Tool-less depth dial for flush, proud or deep driving
- Robust magazine with clear view of remaining nails
- Extra strength top housing for added trade durability
- Rear load magazine with bypass increases reload speed
- Replacement O-Ring kit available (884991)

#### ■Applicable nail sizes:

	mm (in.)
L	50(2) – 90(3-1/2)
d	2.9(.113) – 3.8(.148)
D	6.8(.266) – 7.7(.303)

### NR90AD(H2) 90mm 34° Framing Nailer

08268233



Hanger bracket  
available separately  
**60605X**

## COLATED COIL NAILER

### Specifications

Pressure range	70 – 120 psi
Capacity	200 - 400 nails
Dimensions	274 x 295mm
Weight	1.9kg
Fastener series	16° wire collated or 15° plastic collated coil nails
Standard accessories	Nose protector, safety glasses and carry case



- Smart Fire trigger requires no adjustment between single fire & bump fire
- Tool-less depth dial for flush, proud or deep driving
- 360° adjustable exhaust directs air away from user
- Easy adjustable magazine increases reload speed when changing nail lengths
- Replacement O-Ring kit available (797083)

#### ■Applicable nail sizes:

	mm (in.)	
Nail Type	Wire Collated	Plastic Collated
L	32(1-1/4) – 65(2-1/2)	38(1-1/2) – 57(2-1/4)
d	2.1(.083) – 2.8(110)	2.4(.094) – 2.8(110)
D	4.8(.189) – 6(.236)	5.0(.197) – 6(.236)

### NV65AF3 65mm Wire & Plastic Collated Coil Nailer

08268399



CORDLESS

PNEUMATIC

DRILLING

ROTARY &  
DEMOLITION

FASTENING

GRINDING  
& CUTTING

POLISHING /  
SANDING

SAWING

PLANING /  
ROUTING

AIR  
DISPLACEMENT

ENGINE

ACCESSORIES

## T & F SERIES NAILER

### NT65AB 65mm T & F Series Nailer 08268433



- Bump fire trigger for rapid operation
- Top load magazine ensures quick and easy reloading
- Reduced recoil ensures operator safety and comfort
- Strong robust design for heavy duty trade applications
- Minimal blade witness marks when finish nailing

#### ■ Applicable nail sizes: mm (in.)

L	38(1-1/2) – 65(2-1/2)
d	2.2(.087) – 2.5(.098)
D	6.7(.264) – 8.3(.327)

#### Specifications

Pressure range	70 – 120 psi
Capacity	120 nails
Dimensions	406 x 338mm
Weight	3.0kg
Fastener series	T & F series nails
Standard accessories	Safety glasses, oiler and hex keys



## CONCRETE COIL NAILER

### NC65AC 65mm Concrete Coil Nailer 08268416



- Ambidextrous nail feed valve provides efficient nail advancement
- Reciprocating piston continually hammers nail until fully driven
- Nose cap provides accuracy of nail advancement
- Strong robust design for heavy duty trade applications

#### ■ Applicable nail sizes: mm (in.)

L	38(1-1/2) – 65(2-1/2)
d	2.9(.114) – 3.8(.150)
D	6.7(.264) – 7(.276)

#### Specifications

Pressure range	70 – 120 psi
Capacity	54 nails
Dimensions	394 x 282mm
Weight	2.3kg
Fastener series	Hitachi CV series coil nails
Standard accessories	Nose caps x 2, safety glasses, oiler, hex keys and carry case

